

On page 16, line 9, immediately following "refer" please insert --to--.

IN THE CLAIMS

Please cancel claims 1-32. Please add the following new claims:

- Sub B'
33. A system of communicating information to a predetermined location, the system comprising:
- a transmitter configured to wirelessly transmit a low power signal comprising the information;
  - a transceiver, located remote from, but in close proximity to the transmitter signal and communicate the information to the predetermined location, the transceiver comprising:
    - a line interface circuit configured to interface with a telephone line, wherein the telephone line is part of the public service telephone network (PTSN);
    - and
    - a controller configured to receive the signal and communicate the information over the telephone line; and
    - a central location, located remotely from the transceiver, configured to communicate with the transceiver via the telephone line and receive the information.
34. The system of claim 33, wherein the low power signal further comprises a telephone number such that the transceiver establishes communication with the central location via the telephone number.
35. The system of claim 33, wherein the low power signal further comprises a logical I.P. such that the transceiver can route the information to the central station.
36. system of claim 33, wherein the transmitter is configured to transmit a low power radio frequency (RF) signal.
- Sub D'

37. The system of claim 33, wherein the information comprises a transmitter identifier code, a unique transmission destination address, and a burst transmission length identifier.

38. The system of claim 33, wherein the controller is further configured to communicate a transceiver identification code to the central station.

39. The system of claim 38, wherein the central location comprises means for evaluating the transceiver identification code.

40. The system of claim 39, wherein the evaluating means further determines geographical location of the transceiver based upon the transceiver identification code.

41. The system of claim 33, wherein the central location comprises means for notifying service personnel in response to the information.

42. The system as defined in claim 37, wherein the transmitted signal further comprises:  
a message identification field;  
a packet identification field; and  
a data field.

43. The system as defined in claim 37, wherein the unique transmission destination address is an Internet protocol (IP) address.

44. The system as defined in claim 42, wherein the transmitted signal further comprises:  
a field adaptively configured for data transmission error correction.

45. The system as defined in claim 42, wherein the transmitted signal further comprises:  
a field configured to indicate to a destination device that a subsequent message is to follow.

Sub  
B2  
46.

comprising:

A method for communicating information to a predetermined location, the method comprising:

- wirelessly transmitting an information signal from a transmitter to a remote transceiver, wherein the information signal is a low power signal;
- receiving the information signal by remote transceiver;
- placing a telephone call from the transceiver to a central location via a phone line which comprises part of a public switched telephone network;
- communicating at least a portion of the information signal from the transceiver to the central location; and
- decoding at least a portion of the information signal by the central location.

Account  
47.

The method of claim 46, wherein the method further comprises:

- communicating a transceiver identification code from the transceiver to the central location.

48.

The method of claim 47, wherein decoding further comprises:

- decoding the transceiver identification code.

49.

The method of claim 47, wherein the method further comprises:

- evaluating the transceiver identification code; and

- determining a geographical location of the transceiver based upon the evaluating step.

50.

The method of claim 46, wherein the information signal further comprises a transmitter identification code.

51.

The method of claim 46, wherein the information signal further comprises a telephone number of the central location.

52. The method of claim 46, wherein the information signal further comprises a logical IP address of the central location.

53. The method of claim 50, wherein decoding further comprises:  
decoding the transmitter identification code.

54. The method of claim 53, wherein the method further comprises:  
evaluating the transmitter identification code, and determining a geographic location of the transmitter based upon the evaluating step.

55. A system for communicating information to a central location, the system comprising:  
means for wirelessly transmitting a low powered signal comprising the information;  
means for receiving the low powered signal; the receiving means being remote but within close proximate wireless transmitting means;  
means for telephonically transmitting the information to the central location via a public service telephone network; and  
means for receiving the information at the central location.

56. The system of claim 55, wherein the low powered signal comprises a telephone number, and wherein the means for telephonically transmitting accesses the central location via the telephone number.

57. The system of claim 55, wherein the low powered signal further comprises a logical IP address, and wherein the means for telephonically transmitting accesses the central location via the logical IP address.

58. The system of claim 55, wherein the low power signal is a low power RF signal.

59. The system of claim 55, wherein the low power signal is a low power infrared (IR) signal.

60. The system of claim 55, wherein the low power signal is a low power ultrasound signal.

61. The system of claim 55, wherein the low powered signal comprises a transmitter identifier code, a unique transmission destination address, and a burst transmission length identifier.

62. The system of claim 55, wherein the means for telephonically transmitting further communicates a transceiver identification code of the means for receiving the information.

63. The system of claim 62, wherein the means for receiving the low powered signal further comprises the means for evaluating the transceiver identification code.

64. The system of claim 63, wherein the evaluating means further determines a geographical location of the transceiver.

65. The system of claim 55, wherein the means for receiving the low powered signal further comprises means for notification in response to the information.

66. A transceiver that wirelessly communicates with a transmitter and telephonically communicates with a central location, the transceiver comprising:

a wireless receiver configured to wirelessly receive a low power signal, the low power signal being wirelessly transmitted in close proximity to the receiver, the low power signal comprising encoded information;

a telephonic transmitter configured to transmit a formatted electric signal over a telephone line, the telephone line comprising part of the public switched telephone network (PTSN); and

a controller comprising:

a first portion, connected to the receiver, configured to obtain the information encoded in the received low power signal;

a second portion, connected to the transmitter, configured to deliver the obtained information to the transmitter.

67. The transceiver of claim 66, wherein the controller is a programmable circuit.
68. The transceiver of claim 66, wherein the controller further comprises a look-up table configured to decode the encoded information.
69. The transceiver of claim 66, wherein the low power signal is a low power RF signal.
70. The transceiver of claim 66, wherein the low power signal is a low power IR signal.
71. The transceiver of claim 66, wherein the low power signal is a low power ultrasound signal.
72. A method of relaying an electronic message from a transmitter to a central location, the method comprising:
- wirelessly transmitting an information signal from the transmitter to a remotely located transceiver, the information signal comprising a unique message code, wherein the transmitter is in close proximity to the transceiver;
  - receiving the information by the remotely located transceiver;
  - placing a telephone call from the transceiver to the central location, the central location being identified by a predetermined phone number, over a phone line comprising part of a PTSN; and
  - communicating the unique message code from the transceiver to the central station.
73. A transceiver comprising:
- means for receiving a low powered electromagnetic signal, the electromagnetic signal including an encoded message code;
  - means for transmitting a formatted electric signal over a phone line comprising part of the public switched telephone network (PSTN); and